


MARATHON PRODUCTS

Cryogenic Shipping Containers

CX & CRX Series

Cryo Express (CX) dry shippers are designed to safely transport a variety of materials at cryogenic temperatures. The unique absorbent material prevents a liquid spill if the unit is tipped over. Storage temperature inside the shipping cavity remains at approximately -190C until the liquid nitrogen evaporates from the absorbent material. The CX Series comply with international regulations applicable to the transport of hazardous goods by road (ADR), rail (RID) and by air (IATA-OACI).



MARATHON
PRODUCTS, INC.



Don't ship without us!®

CX & CXR SERIES	CX100	CXR100	CXR500
Static Holding Time ¹ days	24	16	14
Working Time ² days	17	11	7
Evaporation Rate ¹ liters/day	0.18	0.20	0.60
Liquid Nitrogen Capacity liters	4.4	3.3	7.7
Number of Canisters	1	1	N/A
No. of 1.2 ml & 2.0 vials (5/cane) ⁴	85	85	500
No. of 1.2 ml & 2.0 vials (6/cane) ⁴	102	102	500
No. of 1/2 cc straws (10/cane)	280	280	N/A
No. of 1/2 cc straws (Bulk 2 levels)	980	980	N/A
WEIGHT - lb/kg			
Empty	11.7/5.3	11.7/5.3	30/13.6
Full ³	19.5/8.9	18.3/8.3	43.7/19.8
DIMENSIONS - inch/mm			
Neck Diameter	2.8/71.0	3.6/91.0	8.5/216.0
Overall height	18.4/467.0	19.4/493.0	26.9/683.0
Overall Diameter	9.2/234.0	9.2/234.0	15.5/391.0
CAPACITY - inch/mm			
Canister Dimensions	2.64x11/67x2.79	2.64x11/67x2.79	N/A
ACCESSORIES			
Padded Carton P/N	3701-9277	N/A	N/A
5 Shelf Rack P/N	N/A	N/A	RS30-9C44
Poly Carb 100 Box	N/A	R24K-9C44	R24K-9C44
Shipping case	CX10-8C00	CX10-8C00	CP19-8C00

Notes:

1. Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.
2. Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.
3. Without canisters or racks.
4. CXR500 vials are stored in 100 cell boxes.

Please call
1-510-562-6450
for more information.

www.marathonproducts.com
627 McCormick St., San Leandro, CA 94577
sales@marathonproducts.com

Specifications subject to change without prior notice.

